



product Description

With familiar classic globe shape and a great retro style, [INNOLITE Dimmable 7W G80 Globe LED Filament Light Bulb](#) can deliver warm soft ambient light. With innovative LED filament technology, this 7W LED bulb equivalent to an old 60W Incandescent bulb, offers similar brightness but uses around 90% less energy and lasts twenty five times longer.

Meanwhile it also gives a full 360 degree glow and is ideal for living rooms, dining rooms, bed rooms and recreation rooms. Also, unlike standard CFL energy saving lamp, this LED Bulb doesn't contain mercury and switches on instantly.

Installation is very easy due to exact same size and base cap — Just replace your old incandescent bulb with our new INNOLITE LED Filament light bulb directly in your living space and save energy and costs while retaining the traditional look and feel.



Specification

Model No.	37503	
Power	7W	
Cover type	Clear	Frosted
Luminous Flux	806lm ± 10%	750lm ± 10%
Equivalent to Incandescent	60W	
LED Filament Spec.	4 x 50mm	
Input Voltage	220-240VAC or 110-130VAC	
Material	Glass	
Color Temp (CCT)	2700K - 6500K	
Energy Efficiency Label	A++	
Beam Angle	360°	
Color Rendering Index	≥80 Ra	
Power factor	≥0.5	
Start Time	<0.5S	
Switching Cycle	≥12,500	
Life time	Up to 25,000 hours	
Lamp Base	E27 E26 B22	
Dimensions	Dia.= 80mm	
	L= 120mm	



product Certifications



Related Products

Model No.	Wattage(W)	LED Filament Spec.	Luminous Flux(lm)	Equivalent Incandescent Bulb
37501	4W	4 x38	470lm \pm 10%	40W
37505	8W	6 x50	1055lm \pm 10%	75W




Product Test Report

Product Mark

Product Type :
Temperature :22'C
Operator :01
Remark:

Manufacturer :Innotech
Humidity :65%
Test Date :2017-12-29



Chroma Parameters

Chro.Coord.:x=0.4360 y=0.4023 u=0.2507 v=0.3470 duv=-0.0006
CCT: 3002K Dominant Wave.:583.0nm Purity:51.6%
Flux RGB Ratio:R=23.0%,G=74.9%,B=2.0% Peak Wave:605.7nm Half Width:118.7nm

Rendering Index:Ra= 82.6

R1 =81 R2 =94 R3 =93 R4 =81 R5 =85 R6 =94 R7 =79 R8 =56
R9 =6 R10=87 R11=81 R12=78 R13=84 R14=97 R15=73

Photo Parameters

Flux:860.24lm Effi.:134.2lm/W Radiant:2478.2mW Iv:0.0mcd
Efficiency:0.094 Effi Level:A++ (EU 874-2012)

Ele. Parameters

Voltage:U=230.000V Current:I=0.0470A
Power:P=6.41W Power Factor:PF=0.583


Instrument state

Instrument:Hopoo HP8000S Integral Time: 36.296ms VPeak: 13848
VDark: 1097 Scan Range: 380-780nm Product ID: 201710386




product Exhibition

LED Filament Bulb



Features & Advantages





advantages

- ² High brightness 130lm per watt
- ² 360° beam angle delivers a even distribution of light without creating shadows
- ² Up to 90% energy saving with new LED filament technology: 6.5W LED equivalent to 60W incandescent bulb
- ² Retrofit size and classic vintage design for traditional incandescent look and feel
- ² High CRI > 80 ensures more vivid and natural light
- ² Environment friendly: No lead or mercury and No UV or IR Radiation
- ² Long life lasts up to 10 years (4 hours usage per day)
- ² Dimmable
- ² Two years limited warranty based on average daily use of 4 hours
- ² With certification of CE LVD EMC RoHS ErP SAA ETL FCC, etc.



Application

With classic globe shape, [INNOLITE dimmable 7W G80 globe LED filament light bulb](#) can give off a soft warm light. It is suitable for living room, bed room, dining-room, porch, show room, hotel, shop, bistro, restaurant, landscape, exhibition, etc.

Operation and maintenance

- ² Ambient temperature range -20 ° C to 40 ° C.
- ² Store and use the bulb/lamp the same way as traditional bulb/lamp.
- ² Check your fixtures are properly wired and don't deliver voltage spike to bulb/lamp causing overheating/failure.
- ² Bulb/lamp should be kept free from contamination.
- ² Good condition of the lamp-holder contacts is important to ensure proper operation of bulb/lamp.
- ² Switch off mains supply before installing or removing bulb/lamp.
- ² Ensure bulb/lamp is cool before removing.

Warning: Discontinue use if damaged.

Application



Package

1 pc LED bulb per color box, then 40pcs packed in one standard export carton. (1pc/color box, 40pcs per carton)



Return Policy

We provide a free TWO YEARS LIMITED WARRANTY based on average daily use of 4 hours for this item.
Should returns be required:
Step 1) Contact us with this website email.

Step 2) Provide as much detail as possible about the problem you are having.
Step 3) Authorization to return the item will be issued.
Step 4) Return the item for the agreed replacement or refund.



FAQ

Q1. Are you a manufacturer?

A1: Yes, we are an experienced manufacturer with custom molds and production lines.

Q2.How about product quality?

A2: Our technicians and QC teams test the products one by one using aging line, professional devices and instruments to ensure the quality of all products.Q3.How about the price?

A3: We are a manufacturer and always offer our customers the most competitive prices.

Q4. Do you order?

A4: Contact with online service or send us an e-mail immediately, we will reply soon to product price, specifications, packaging, etc. Tack.Q5. Can I buy samples from you?

A5: Yes! You are welcome to place test orders to test our superior quality and service, mixed samples are acceptable.

Q6. Can I visit your factory?

A6: Yes, welcome to visit our factory at your appropriate time.

Q7. How can I make OEM or ODM orders?

A7: We have different print jobs for different OEM / ODM orders. Please contact us with online service or email us directly.

Q8. How do I pay for my orders?

A8: You can pay with T / T, L / C at the point of view would be available to qualified bank and MOQ required for each order.

Logistics

Sample order ship by DHL, UPS, FedEx, TNT, EMS etc

For mass order delivery, can be optional with terms of Exwork, FOB, CNF, CIF by air or by sea based on the buyer's forwarder or ours



Certifications



Exhibition & Fair



Factory Show

