



Product Description

With a elegant pineapple shape design, INNOLITE pineapple antique Edison filament LED bulb is perfect for landscape lighting and mood lighting. It delivers a warm glow that creates an ambiance that sets a welcoming tone in any setting.

With high quality LED([Pineapple shape LED light bulb supplier](#)) filaments, this bulb is more energy saving than traditional incandescent bulbs with the similar brightness but lasts 25 times longer. It is easy to Install as easily as installing the incandescent bulbs as with the same base cap E26 E27, you can replace the old bulbs in a few seconds.

With integration of traditional bulb characteristics, this bulb is better for heat dissipation than the traditional tungsten lamp and is mercury-free and no UV or IR radiation.



Product Specification

Model No.	38072
Power	4W
Cover type	Amber or Smoke
Luminous Flux	320lm ± 10%
LED Filament Spec.	4X38
Input Voltage	220-240VAC or 110-130VAC
Material	Glass
Color Temp (CCT)	1800K - 3000K
Energy Efficiency Class	A+
Beam Angle	360°
Color Rendering Index	≥80 Ra
Power factor	≥0.5
Start Time	<0.5S
Switching Cycle	≥12,500
Life time	Up to 25,000 hours
Lamp Base	E27 E26 B22
Dimensions	Dia.=95mm
	L=135mm



Product Certificates

CE RoHS ErP SAA  FC



Related Products

Model No.	Bulb Type	Dimension	Wattage(W)	Luminous Flux(lm)
38071	Pineapple	Ø95x135mm	2W	160lm ± 10%
38073			6W	450lm ± 10%

38091	Football	Ø100x130mm	2W	160lm ± 10%
38092			4W	320lm ± 10%
38093			6W	450lm ± 10%



Product Test Report

Product Mark

Product Type :904-479

Temperature :26'C


Operator :01

Remark:

Manufacturer :Innotech

Humidity :65%

Test Date :2017-12-29



Chroma Parameters

Chro.Coar.:x=0.4625 y=0.4117 u=0.2637 v=0.3521 duv=0.0002

CCT: 2673K Dominant Wave.:584.3nm Purity:62.4%

Flux RGB Ratio:R=25.3%,G=73.3%,B=1.4% Peak Wave:607.7nm Half Width:115.0nm

Rendering Index:Ra= 82.0

R1 =80	R2 =92	R3 =95	R4 =80	R5 =82	R6 =92	R7 =80	R8 =56
R9 =7	R10=82	R11=79	R12=75	R13=83	R14=98	R15=72	

Photo Parameters

Flux:443.52lm

Effi.:121.2lm/W

Radiant:1301.4mW

Iv:0.0mcd

Efficiency:0.092

Effi Level:A++ (EU 874-2012)

Ele. Parameters

Voltage:U=230.100V

Current:I=0.0280A

Power:P=3.66W

Power Factor:PF=0.551

Instrument state

Instrument:Hopoo HP8000S

Integral Time: 63.588ms

VPeak: 13320

VDark: 1249

Scan Range: 380-780nm

Product ID: 201710386



Product show

Vintage LED Filament Bulb



Features & Advantages





Advantages

- ² Exact retrofit for incandescent bulb
- ² 360° beam angle delivers a even distribution of light without creating shadows
- ² Up to 85% energy saving with new LED([china pineapple antique Edison filament LED bulbs](#)) filament technology
- ² No flicker to protect human eyes
- ² High CRI > 80 ensures more vivid and natural light
- ² Environment friendly: No lead or mercury and No UV or IR Radiation
- ² Long life time lasts up to 10 years (4 hours use per day)
- ² Dimmable
- ² Two years limited warranty based on average daily use of 4 hours
- ² With certification of CE LVD EMC RoHS ErP SAA ETL FCC, etc



Application

INNOLITE pineapple antique Edison filament LED([pineapple LED bulb](#)) bulbs can deliver a classic ambiance light in living room, bedroom, hallway, exhibition hall, showroom, showcase, art-room, museums, bar, bistro, coffee shop,cafes, restaurant, hotel, etc. It is ideal for landscape lighting, mood lighting, etc.

Operation and maintenance

- ² Ambient temperature range -20° C to 40°C.
- ² Store and use the bulb/lamp the same way as traditional bulb/lamp.
- ² Check your fixtures are properly wired and don't deliver voltage spike to bulb/lamp causing overheating/failure.
- ² Bulb/lamp should be kept free from contamination.
- ² Good condition of the lamp-holder contacts is important to ensure proper operation of bulb/lamp.
- ² Switch off mains supply before installing or removing bulb/lamp.
- ² Ensure bulb/lamp is cool before removing.

Warning: Discontinue use if damaged.

Application



Package

1 pc LED bulb per color box, then 50pcs packed in one standard export carton.(1pc/color box, 50pcs/carton)



Return Policy

We provide a free TWO YEARS LIMITED WARRANTY based on average daily use of 4 hours for this item. Should returns be required:

Step 1) Contact us with this website email.

Step 2) Provide as much detail as possible about the problem you are having.

Step 3) Authorization to return the item will be issued.

Step 4) Return the item for the agreed replacement or refund.



FAQ

Q1.Are you a manufacturer?

A1: Yes, we are an experienced manufacturer with our own molds and production lines.

Q2.How about quality of products?

A2: Our technicians and QC teams test the products one by one using aging line, professional devices and instruments to ensure the quality for all products.

Q3.How about price?

A3: We are a manufacturer and always offer our customers the most competitive prices.

Q4.How to place an order?

A4: Contact with online service, or sent email to us directly, we will reply to you with product price, specifications, packing etc. soon. Thank you.

Q5.May I buy samples from you?

A5: Yes! You are welcome to place sample order to test our superior quality and service, mixed samples are acceptable.

Q6.Can I visit your factory?

A6: Yes, welcome to visit our factory at your convenient time.

Q7.How can I make OEM or ODM orders?

A7: We have different print processing for different OEM/ODM orders. Please contact us with online service or send email to us directly.

Q8. How should I pay for my orders?

A8: You can pay by T/T, L/C at sight would be available for qualified bank and MOQ required for each order.

Logistics

Sample order ship by DHL, UPS, FedEx, TNT, EMS etc

For mass order delivery, can be optional with terms of Exwork, FOB, CNF, CIF by air or by sea based on the buyer's forwarder or ours



Certifications



Exhibition & Fair



Factory Show

