# product Description

INNOLITE BK Style COB LED Floodlight(LED Floodlight manufacturer china) can provide a diffuse and versatile lighting effect with innovative exterior design. And with a superior optical lens with strong transmittance, this 120 degree headlight lamp will focus on areas highlighting needs with maximum efficiency. It can be better integrated with the architectural landscape, perfect fusion of the application environment.

Product seal is perfect. With IP classification IP65, Innolite LED Floodlight(LED Floodlight supplier) is suitable for outdoor lighting, gardens, squares, signs, factories, dolls, arenas, etc. It comes with adjustable metal mount to adjust the different angles and can be installed in the ceiling, walls, ground and other places.



# Specification

model no.	33625			
Force	100W			
brightness	90 lm / w			
LED type	СОВ			
Input voltage	190-260VAC or 85-265VAC			
Material of bag	Aluminum			
Color Temp (CCT)	2700K - 6500K			
Energy efficiency class	A +			
Beam Angle	120 degrees			
Color rendering index	& Gt; 80 Ra			
Power factor	& Gt; 0.95			
start time	& Amp; lt; 0.5s			
switching Cycle	≥12,500			
Lifetime	Up to 50,000 hours			
Temp. of the operation	-30 ~ + 50 ° C			
IP classification	IP65			
Measure	285x255x75mm			



# product Certifications

# ( RoHS



# **Related Products**

model no.	product name	Wattage	Material of cases	brightness	Measure


33621	LED headlight BK Style COB	10W	Aluminum	90 lm / w	130x110x41 mm
33622		20W	Aluminum	90 lm / w	181x158x50 mm
33623		30W	Aluminum	90 lm / w	196x172x52 mm
33624		50W	Aluminum	90 lm / w	240x210x60 mm
33626		150W	Aluminum	90 lm / w	345x310x80 mm
33627		200W	Aluminum	90 lm / w	380x349x97 mm
33628		300W	Aluminum	90 lm / w	430x480x140 mm



# Advanced Heat sink design Quality aerospace die-casting aluminum High quality COB LED Toughened glass mask Stainless Steel screw Waterproof IP65



# Feature & Advantages





- <sup>2</sup> Use the most effective integrated aluminum alloy, the finished lamp can work over 50,000 hours
- <sup>2</sup> Heat source in different sizes from 10-300W for varied lighting requirements.
- <sup>2</sup> Protection rate: IP65 for indoor and outdoor lighting.
- <sup>2</sup> No flicker to protect human eyes
- <sup>2</sup> Nothing buzzing and immediately on
- <sup>2</sup> High CRI & gt; 80 guarantees more vibrant and natural light
- <sup>2</sup> Environmentally friendly: No lead or mercury and no UV or IR radiation
- <sup>2</sup> Long life lasts up to 17 years (4 hours usage per day)
- <sup>2</sup> Two-year limited warranty based on average daily use of 4 hours
- <sup>2</sup> With certification of CE RoHS, etc.



# **Application**

Innolite 100W Aluminum COB Black LED Floodlight(<u>LED Floodlight on sale china</u>) BK Style With 120 Degree Radiation Angle LED Floodlight can give you a diffuse and versatile lighting effect with slim conventional fixture. It is widely used in gardens, building façades, bridges, tunnels, stadiums, signs, park sculpture, toll station, gas station, factory, warehouse, big supermarket, exhibition hall, etc.

# **Application**







### safety

- <sup>2</sup> Working temperature range -30 ° C to 50 ° C
- <sup>2</sup> Check the lamp before installation, if no damage occurs during transport, do not install.
- $^{\rm 2}$  Maintenance should be carried out by a person familiar with the pipe.
- <sup>2</sup> Do not place any objects on the lamp.
- <sup>2</sup> Keep the lamp away from flame or high temperature objects.
- <sup>2</sup> For indoor use only.
- <sup>2</sup> Replace only with the same type of LED tube. Risk of electric shock.
- <sup>2</sup> If the glass lamp tube is broken, the lamp must be removed immediately.

### maintenance Descriptions

- <sup>2</sup> Disconnect the lamp from the power supply before servicing.
- <sup>2</sup> Clean the luminaires with a dry cloth.
- <sup>2</sup> Do not clean the lamp with corrosive chemicals.

### Warning: Cancel use if it is damaged.

### **Package**

1 LED light per color box, 20 pcs packed in a regular export carton. (1 pc / color box, 20 pcs / carton)



# return Policy

We provide a free two-year LIMITED WARRANTY based on the average daily use of 4 hours for this product. Should return be required

- Step 1) Contact us with this site's email.
- Step 2) Give as much detail as possible about the problem you have.
- Step 3) Permission to return the item will be issued.
- Step 4) Return the item for the agreed replacement or refund.



- Q1. Are you a manufacturer?A1: Yes, we are an experienced manufacturer with custom molds and production lines.
- Q2. How about product quality?
- A2: Our technicians and QC teams test the products one by one with the help of aging line, professional devices and instruments to ensure the quality of all products. Q3. How about the price?
- A3: We are a manufacturer and always offer our customers the most competitive prices.
- Q4. Do you order?
- A4: Contact with online service or send us an e-mail immediately, we will reply soon to product price, specifications, packaging, etc. Thanks.
- Q5. Can I buy samples from you?
- A5: Yes! You are welcome to place test orders to test our superior quality and service, mixed samples are acceptable.
- Q6. Can I visit your factory?
- A6: Yes, welcome to visit our factory at your appropriate time.
- Q7. How can I make OEM or ODM orders?
- A7: We have different print jobs for different OEM / ODM orders. Please contact us with online service or email us directly.
- Q8. How do I pay for my orders?
- A8: You can pay with T / T, L / C at the point of view would be available to qualified bank and MOQ required for each order.



Sample order ship by DHL, UPS, FedEx, TNT, EMS etc. For mass order delivery, can be optional with terms of Exwork, FOB, CNF, CIF by air or by sea based on the buyer's forwarder or ours



### \* Certifications



### Exhibition & Fair



### Factory Show

